

# Polycom SoundPoint IP Expansion Module Specifications

## Display

- 160 x 320 pixel grayscale graphical LCD

## Feature Keys

- 14 multifunctional line keys automatically configurable as a line registration, call appearance, speed dial, DSS, or BLF<sup>1</sup> key
- Dual-color (red or green) illuminated LEDs for line status information

## Protocol Support<sup>2</sup>

- IETF SIP (see the SoundPoint IP 601 data sheet for details)

## Compatible SoundPoint IP Models

- SoundPoint IP 601

## Connection with the Host Phone

- IrDA Protocol
  - Compliant to Serial Infrared Physical Layer Link SIR data rate (115.2kbits/s)
  - Activated upon attachment to host SoundPoint IP phone

## Power

- The Expansion Module is powered by the host phone
  - Host phone powering options: IEEE 802.3af PoE or through an external AC adapter (24V DC @ 500mA minimum)
- Powering starts automatically upon connection
- No additional power source is required

## Expandability

- Up to 3 Expansion Modules can be attached to the host SoundPoint IP 601 phone to provide a high-performance attendant console with 48 multifunctional line keys and 4 high-resolution LCD displays

## Feature Support

- Local feature-rich GUI with animation
- Shared call appearance, bridged line appearance (Key System emulation)
- Multiple call appearances
- Flexible line appearance (requires SIP 1.5.x or later)
- Multilingual user interface (driven from the host SoundPoint IP 601 phone)
  - Chinese
  - Danish
  - Dutch
  - English (Canada)
  - English (UK)
  - English (US)
  - French
  - German
  - Italian
  - Japanese
  - Korean
  - Norwegian
  - Portuguese
  - Russian
  - Spanish
  - Swedish

## Approvals

- EMI/EMC Approvals under host SoundPoint IP 601 phone

## Safety

- UL 1950
- CE Mark
- CSA C22.2 No.950
- EN60950.1

## Operating Temperature

- +10 to +40 degrees C (+50 to +104 degrees F)

## Relative Humidity

- 20% to 85%, non-condensing

## Storage Temperature

- -40 to +70 degrees C (-40 to +160 degrees F)

## SoundPoint IP Expansion Module Comes With:

- SoundPoint IP Expansion Module console
- SoundPoint IP Expansion Module base stand
- Quick Start Guide
- Product registration card

## Size

- 5 in x 5 in x 6.5 in x 2.5 in (12.5 cm x 12.5 cm x 16 cm x 6 cm) (W x H x D x T)

## Weight

- Shipping: 1.30 lb (0.6kg)

## Part Numbers / UPC Codes

- 2200-11700-025 / 6108 0702 2695

## Unit Box Dimensions / Weight

- 11 in x 6.5 in x 3.5 in / 580g

## Master Carton Quantity

- Ten

## Country of Origin

- Thailand

## Warranty

- 1 year



<sup>1</sup> The Busy Lamp Field (BLF) feature is subject to future implementation

<sup>2</sup> The SoundPoint IP 601 and Expansion Module both require SIP version 1.6.2 or higher

©2005 Polycom, Inc. All rights reserved.

Polycom, the Polycom logo and SoundPoint are registered trademarks of Polycom, Inc. All other trademarks are the property of their respective owners. Information in this document is subject to change without notice.



### Polycom Headquarters:

4750 Willow Road, Pleasanton, CA 94588 (T) 1.800.POLYCOM (765.9266) for North America only.  
For North America, Latin America and Caribbean (T) +1.925.924.6000, (F) +1.925.924.6100

### Polycom EMEA:

270 Bath Road, Slough, Berkshire SL1 4DX, (T) +44 (0)1753 723000, (F) +44 (0)1753 723010

### Polycom Asia Pacific:

Polycom Hong Kong Ltd., Rm 1101 MassMutual Tower, 38 Gloucester Road, Wanchai, Hong Kong, (T) +852.2861.3113, (F) +852.2866.8028

Part No. 3726-17369-001 Rev. 9/05